


GD-2809 parameter list

Bass speaker:	Double 8 inches	80 Magnetic	THD+N 10%		
high-pitched speaker:	3 inches				
Frequency response:	80HZ~20KHz				
Signal-to-noise ratio S/N:	≥80DB Distortion THD: ≤5%				
Bluetooth Specifications:	Zhongke AB5301A	Bluetooth version:	V5.0		
Transmission range: 10 meters Transmission frequency: 2.4GHz					
Amplifier IC:	CS8623		Maximum output power: 40W		
Function:					
Bluetooth Interconnection (TWS)	support		music pitch adjustment	support	
Bluetooth playback	support		microphone reverb	support	
FM radio	support		Microphone volume adjustment	support	
TF card function	support		3.5MM audio input interface	support	
USB input	Support up to 64G		guitar input	not support	
music format	Full format support		remote control.	support	
One key to cancel the original sound	support		Wired microphone input	support	
microphone priority	support		Wireless microphone input	support	
One-click bass	not support		lantern switch	support	
recording	support		lighting effects	Symphony Light Circle	
Built-in EQ	Support (requires remote control)		External battery input (DC12V)	support	
Loop	Support (requires remote control)		Built-in power strip	not support	
battery capacity:	4.5Ah	without battery protection		While charging and support	
Charging voltage:	DC 15V		Charging time:	About 4-6 hours	
Standby time: more than 10 hours					
Music time: about 2-3 hours (when playing at 80% volume)			Tripod hole	Note:	
Pull rod:	two sections		wheel:	ABS plastic wheel	
weight:	N7.35KG/G8.45KG		Accessories:	wireless microphone	charger
Product Size:				manual	
Inner packing size:	5-layer color box 312*311*641MM		Foam:	Foam	
Package size:			Packing Quantity:	Taiwan/Case	