GD-2810 parameter list

Bass speaker:	Double 8 inches 80 Magnetic		TH	D+N 10%		
high-pitched speaker:		3 inches				
Frequency response:	80HZ~20KHz					
Signal-to-noise ratio S/N:	≥80DB Distortion THD: ≤5%					
Bluetooth Specifications: Zhongke AB5312B		Bluetooth version:		V5. 0		
Transmission range: 10 meters Transmission fre		requency: 2.4GHz				
Amplifier IC: CS8370				imum output power: 30W		Man min
Function:						
Bluetooth Interconnection (TWS)		support		music pitch adjustment		not support
Bluetooth playback		support		microphone reverb		support
FM radio		support		Microphone volume a	djustment	support
TF card function		support		3.5MM audio input i	nterface	support
USB input		Support up to 64G		guitar input		not support
music format		Full format support		remote control.		support
One key to cancel the original sound		not support		Wired microphone in	put	support
microphone priority		not support		Wireless microphone	e input	support
One-click bass		not support		lantern switch		support
recording		support		lighting effects		flame lamp
Built-in EQ		Support (requires remote control)		External battery input (DC12V)		not support
Loop		Support (requires remote control)		Built-in power strip		not support
battery capacity:	8000mAH with battery protection			While charging and support		
Charging voltage: DC 5V				Charging time: About 5-		hours
Standby time: more than 10 hours						
Music time: about 2-3 hours (when playing at 80% volume)			Tripod hole	none	Note:	
Pull rod:	Without			wheel:	ABS plastic wheel	
weight:	N7. 54/G8. 99KG				wireless microphone	Charging Cable
Product Size:	345*305*714mm			Accessories:	manual	
Inner packing size:	nner packing size: 5-layer color box 453*353*653MM			Foam: Foam		
Package size:				Packing Quantity:		Taiwan/Case