LT-2212A parameter table

		221211 parameter table				
Bass speaker:	12 inches*2		TH	ID+N 10%		2011 July 12700
high-pitched speaker:	3 inches					
Frequency response:	80HZ~20KHz					\
Signal-to-noise ratio S/N:	≥80DB Distortion THD: ≤5%					`
Bluetooth Specifications:	Zhongke AB5301A Bluetooth version:			V5.0		,
Transmission range: 10 meters Transmission frequency: 2.4GHz						
Amplifier IC:		Max	ximum output power:	****		
		Function:				
Bluetooth Interconnection (TWS)		support		music pitch adjustment		support
Bluetooth playback		support		microphone reverb		support
FM radio		support		Microphone volume	adjustment	support
TF card function		support		3.5MM audio input	interface	support
USB input		Support up to 64G		guitar input		support
music format		Full format support		remote control. Wired microphone input		support
One key to cancel the original sound		support				support
microphone priority		support		Wireless microphone input		support
One-click bass		not support		lantern switch		support
recording		support		lighting effects External battery input (DC12V)		screen light
Built-in EQ		Support (requires remote control)				support
Loop		Support (requires remote control)		Built-in power strip		support
battery capacity:	9Ah	without battery protection		While charging and support		
Charging voltage: DC 5V charging time about 4 hours DC 15V		C		Charging time:	About 4-6	6 hours
Standby time: more than 10 hours						
Music time: about 2-3 hours (when playing at 80% volume)				Tripod hole		Note:
Pull rod:	Without			wheel: small iron wheel		
weight:	N18/G19.5KG				wireless microphone	Charging Cable
Product Size:	373*270*1033mm			Accessories:	manual	big remote
Inner packing size:	418*316*1066mm	5 layers of K=A double reinforced kraft paper		Foam:	Foam	
Package size:				Packing Quantity:		Taiwan/Case